







# Installation Instruction for Using EZ-Retractable Coupler (RS-677) And Spring Loaded Idler




## 1. Prepare all the components for two shades (Fig.1):




- 1) Assemble drives and crowns with EZ-Retractable Coupler according to page M-6;
- 2) Cut fabric perfectly with right angles (90°), and fabric length of shades should be the same (Fig.2&3);
- 3) Attach fabric with bottom bar to tube along step line, roll fabric all the way up (Fig. 4);




- 4) Insert the fork shaft coupler into 2nd (idler) shade tube right side, refer to Fig. 5 step a), b) & c).
- a) Align the key on drive with groove on tube and slide into tube.
  - b) Keep the slot of the fork shaft horizontally and retract the shaft in.




- 5) Insert the tang shaft coupler into 1st (motor) shade tube left side, refer to Fig.6 step a), b) & c).
- a) Open 1st shade to same fabric drop length A as 2nd shade.
  - b) Insert the tang shaft coupler into 1st shade tube with its tang shaft horizontally. **If the drive keyway does not align with tube groove, rotate the tang shaft coupler 180° (This applies for using 2 3/8" tube only).**




2. Attach the motor and idler brackets to the ceiling, wall, window frame or molding. Then attach the intermediate bracket loosely so it can be adjusted later.




3. Install motor side shade first: insert motor end into the motor bracket and make sure it is locked by spring ring.




4. Slide loosely tightened intermediate bracket to the tang shaft until it stopped by the should of tang shaft, then tighten the intermediate bracket.




5. Install idler shade: a) insert the spring idler into the idler bracket and push shade toward idler bracket; b) align the fork shaft with the tang shaft, make sure fabric drop lengths are the same; c) release the fork shaft into the interm. bracket, be sure tang&fork shaft joint together



6. Shades installed completely.



7. Fully drop shades to check their bottom bar



**Note:**  
If bottom bars are not leveled, please refer to the page of How to Use EZ-Adjustable /Retrac. Coupler to Level Bottom Bars.